

# HYBRID HAY RUNNER



## High Capacity Carted Rake

- High-clearance frame
- Narrow transport
- Adjustable tongue length
- Easy rake angle adjustment
- 15" tires
- Front wheel lock up
- Single side raking
- Windrow width adjustment
- Heavy-duty frame
- 3.5" x 8" Hydraulic cylinders
- 55" Rake wheels with 7mm rake teeth
- Adjustable tongue clevis
- Optional center wheel kit
- Optional windguards
- Optional tandem axles



# SPECIFICATIONS

# HYBRID HAY RUNNER

Standard Rear Hinging Option	HR8 HR8H	HR10 HR10H	HR12 HR12H
Raking width*	16' to 19'	18' to 21'	20' to 23'
Number of wheels	8	10	12
Weight	1,9460 lbs.	2,115 lbs.	2,280 lbs.
Transport width	8' to 9'5"		
Transport length**	19'3" with tongue at minimum setting		
Transport height***	8' to 9'5"		
Wheel hubs & bearings	Greaseable tapered roller bearings		
Wheel diameter	55"		
Tine diameter	7MM		
Tines per wheel	40		
Rake wheel suspension	Independent arm for each wheel - Teflon bushings at pivot		
Ground pressure adjustment	Adjustable torsion spring on each wheel		
Hydraulic cylinders	2 - 3½" x 8" double acting		
Hydraulic pressure requirement	Minimum 1900 PSI		
Hydraulic remotes required	1 set		
Tires	205/75-R15" Radial		
Hydraulic center wheel kit	Optional		
Walking Tandem Axles	Optional		
Wind Guards	Optional		

\*Varies depending on crop condition

\*\*Varies depending on tongue adjustment

\*\*\*Varies depending on rake adjustment



MANUFACTURED BY **OGDEN**  
Metalworks, Inc.

[www.ogdenequipment.com](http://www.ogdenequipment.com)

PO Box 128 | 301 N Marilyn Ave.  
Ogden, IL 61589  
217-582-2552